
Wesco Industries Ltd. PowerStrand Wire Rope




7 x 7 Class Coated Lifeline Wire Rope

Stainless Steel 6 Outer Strands, Rotation Wire Rope

Coated lifeline wire ropes are used mainly for safety lifeline wires on yachts, power /sail boats and other guard rail applications. The PVC Coating provides protection against the sunlight, while the increased Coating provides extra protection against rubbing and scrubbing, and the 7 x 7 construction provides a stiffness and low stretch that is required for guard rails.

Wire Rope Diameter Inches	Outside Diameter Inches	Weight per Foot Pounds	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds
1/8	1/4	0.04	316	W70704SP-WHITE	1,500
3/16	5/16	0.10	316	W70706SP-WHITE	3,100



Stainless Steel 1 x 19 Strand

A stiff spiral strand construction suitable for standing rigging. Applications can include yacht / sailboat rigging, architectural, guying, balustrading, cable railing and display.

1x19, Load bearing outer wires 12

Fill factor 0.76

Use of swivel is not permitted, not suitable for overhead lifting.

Diameter Inches	Weight per Foot Pounds	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds
1/16	0.01	316	W11902S1C-316	400
3/32	0.02	316	W11903S1C-316	1,000
1/8	0.04	316	W11904S1C-316	1,780
5/32	0.06	316	W11905S1C-316	2,800
3/16	0.08	316	W11906S1C-316	4,000
1/4	0.14	316	W11908S1C-316	6,900
5/16	0.21	316	W11910S1C-316	10,600
3/8	0.30	316	W11912S1C-316	14,800





