


6 x 19 Class Coated Wire Rope

Galvanized 6 Outer Strands, Rotation Wire Rope

Galvanized PVC Coated Cables are excellent for outdoor applications with direct sunlight or wet locations. The coating for this particular rope is oversized for increased protection against the environment and wear. It is used for general multi purpose rigging such as safety cables, mooring applications, security cables and hanger ropes.

Wire Rope Diameter Inches	Outside Diameter Inches	Weight per Foot Pounds	Wesco Stock Code	Minimum Strength Pounds	Colours Stocked
1/2	3/4	0.70	W61916BP	23,940	Orange



1 x 7 Guy Wire

Galvanized Strand

A stiff strand construction suitable for Guy Strand Rigging, Fish Enclosure Netting, Fishing Boat Rigging, Guy and Stay Ropes.

1x7, Load bearing outer wires 6

Fill factor 0.78

Use of swivel is **not** permitted, not suitable for overhead lifting.

Diameter Inches	Weight per Foot Pounds	Finish	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds
3/16	0.08	Galvanized	EHS	W10706G1C	4,000
1/4	0.13	Galvanized	EHS	W10708G1C	6,400
5/16	0.22	Galvanized	EHS	W10710G1C	11,100
3/8	0.27	Galvanized	EHS	W10712G1C	13,500
7/16	0.39	Galvanized	EHS	W10714G1C	19,500
1/2	0.52	Galvanized	EHS	W10716G1C	25,500

