

## 6 x 24 FC Class Wire Rope

### 6 Outer Strands, Rotation Wire Rope


An inexpensive galvanized wire rope which is very flexible and suitable for cargo runners, mooring lines, lifting slings, lashing, fishing and tow lines.

6x24 (15+9+FC) FC, Load bearing outer wires 144

Fill factor 0.41

Use of swivel is **not** permitted.

Diameter Inches	Weight per Foot Pounds	Finish	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds
1/4	0.09	Galvanized	EIPS	W62408D1C	4,980
5/16	0.14	Galvanized	EIPS	W62410D1C	7,620
3/8	0.20	Galvanized	EIPS	W62412D1C	9,540
7/16	0.27	Galvanized	EIPS	W62414D1C	14,110
1/2	0.35	Galvanized	EIPS	W62416D1C	19,320
9/16	0.44	Galvanized	EIPS	W62418D1C	24,200
5/8	0.54	Galvanized	EIPS	W62420D1C	28,600
3/4	0.78	Galvanized	EIPS	W62424D1C	40,900
7/8	1.06	Galvanized	EIPS	W62428D1C	55,400
1	1.38	Galvanized	EIPS	W62432D1C	75,400
1-1/8	1.75	Galvanized	EIPS	W62436D1C	90,640
1-1/4	2.16	Galvanized	EIPS	W62440D1C	116,600



## 7 x 7 x 7 Class Wire Rope

### Cable Laid

Cable laid ropes are specifically designed to give superior flexibility for use as sling assemblies and log wrapper cables.

7x7x7 (6+1x6+1x6+1), Load bearing outer wires 294

Use of swivel is **not** permitted.

Diameter Inches	Weight per Foot Pounds	Finish	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds
5/16	0.14	Galvanized	EIPS	W77710B1C	7,000
3/8	0.27	Galvanized	EIPS	W77712B1C	14,300
7/16	0.36	Galvanized	IPS	W77714B1C	13,800
1/2	0.37	Galvanized	EIPS	W77716B1C	18,100
9/16	0.44	Galvanized	EIPS	W77718B1C	29,700