


## ProCraft Grade 100 Swivel Self Locking Hooks

These self locking hooks are suitable for overhead lifting in a wide variety of applications. Commonly used with overhead lifting chain assemblies, but with an oversized swivel eye it can be used for wire rope bridles, web slings bridles and synthetic rope assemblies. The swivel eye is for positioning only, and will not swivel under load. The trigger kit is recessed for increased safety, and will only release when unloaded. The hook will close when loaded and will remain closed until unloaded. Manufactured and proof load tested to EN 1677-4, and individually marked with manufacturer and batch code numbers that complies with or exceeds ASTM standards.

Stock Code	Number Code	Nominal Size	Working Load Limit Pounds 4:1 FOS	Working Load Limit Pounds 5:1 FOS	Dimension Inches									Weight per Piece Pounds
					A	B	C	D	E	F	G	H	I	
71HSA-SE1008PR	P521H	9/32 & 5/16	5,700	4,560	1.2	0.6	1.3	7.5	1.0	3.4	1.3	9.1	0.9	3.1
71HSA-SE1012PR	P521H	3/8	8,800	7,040	1.6	0.6	1.7	9.1	1.3	4.4	1.8	11.0	1.1	5.0
71HSA-SE1016PR	P521H	1/2	15,000	12,000	1.9	0.9	2.0	11.3	1.6	5.4	2.0	13.8	1.3	9.8
71HSA-SE1020PR	P521H	5/8	22,600	18,080	1.9	0.9	2.4	13.1	2.1	6.8	2.5	16.1	1.7	18.0



## ProCraft Grade 100 Swivel Bearing Self Locking Hooks

These self locking hooks are suitable for overhead lifting in a wide variety of applications. Commonly used with overhead lifting chain assemblies, but with an oversized bearing swivel eye it can be used for wire rope bridles, web slings bridles and synthetic rope assemblies. The bearing swivel allows full rotation while under load. The trigger kit is recessed for increased safety, and will only release when unloaded. The hook will close when loaded and will remain closed until unloaded. Manufactured and proof load tested to EN 1677-4, and individually marked with manufacturer and batch code numbers that complies with or exceeds ASTM standards.

Stock Code	Number Code	Nominal Size	Working Load Limit Pounds 4:1 FOS	Working Load Limit Pounds 5:1 FOS	Dimension Inches									Weight per Piece Pounds
					A	B	C	D	E	F	G	H	I	
71HSA-SEB1008PR	P521BH	9/32 & 5/16	5,700	4,560	1.2	0.6	1.3	7.4	1.0	3.4	1.3	9.1	0.9	3.4
71HSA-SEB1012PR	P521BH	3/8	8,800	7,040	1.6	0.6	1.7	9.0	1.3	4.4	1.8	11.0	1.1	5.5
71HSA-SEB1016PR	P521BH	1/2	15,000	12,000	1.9	0.9	2.0	11.2	1.6	5.4	2.0	13.8	1.3	10.1
71HSA-SEB1020PR	P521BH	5/8	22,600	18,080	1.9	0.9	2.4	13.2	2.1	6.8	2.5	16.1	1.7	18.2
71HSA-SEB1024PR	P521BH	3/4	35,300	28,240	2.7	1.06	3.1	14.8	2.5	7.9	3.0	18.5	1.9	27.8