

## 7 x 7 & 7 x 19 Class Wire Rope

### Galvanized 6 Outer Strands, Rotation Wire Rope

A commercial grade aircraft cable that makes for a very good all round small diameter rope. It is suitable for many applications including marine ropes, stage rigging, winch ropes, pulling cables, assemblies, seismic bracing and control Cables.

7x7 (6+1) WSC, Load bearing outer wires 42

Fill factor 0.55


7x19 (12+6+1) WSC, Load bearing outer wires 114

Fill factor 0.57

Manufactured to US Federal Specification RR-W-410F

Use of swivel is **not** permitted.

Diameter Inches	Weight per Foot Pounds	Grade Tensile	7 x 7 Construction		7 x 19 Construction	
			Wesco Stock Code	Minimum Strength Pounds	Wesco Stock Code	Minimum Strength Pounds
3/64	0.01	IPS	W70701B5C	270	~	~
1/16	0.01	IPS	W70702B5C	480	~	~
3/32	0.02	IPS	W70703B5C	920	~	~
1/8	0.03	IPS	W70704B5C	1,700	W71904B5C	2,000
5/32	0.05	IPS	~	~	W71905B5C	2,800
3/16	0.07	IPS	~	~	W71906B5C	4,200
7/32	0.09	IPS	~	~	W71907B5C	5,600
1/4	0.11	IPS	~	~	W71908B5C	7,000
5/16	0.17	IPS	~	~	W71910B5C	9,800
3/8	0.24	IPS	~	~	W71912B5C	14,400
1/2	0.41	IPS	~	~	W71916B5C	24,000
5/8	0.65	IPS	~	~	W71920B5C	37,000



## 7 x 19 Garage Door Rope

### Galvanized 6 Outer Strands, Rotation Wire Rope

A commercial grade aircraft cable which is flexible and has a lightly lubricated core. This cable is also cycle tested to ensure longevity in high cycle environments such as garage door and multiple sheave applications.

7x19 (12+6+1) WSC, Load bearing outer wires 114

Fill factor 0.57

Manufactured to US Federal Specification RR-W-410F

Use of swivel is **not** permitted.

Diameter Inches	Weight per Foot Pounds	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds
1/8	0.03	IPS	W71904B5C-DCQ	2,000
5/32	0.05	IPS	W71905B5C-DCQ	2,800
3/16	0.07	IPS	W71906B5C-DCQ	4,200