


7 x 7 Class Coated Lifeline Wire Rope

Stainless Steel 6 Outer Strands, Rotation Wire Rope

Coated lifeline wire ropes are used mainly for safety lifeline wires on yachts, power /sail boats and other guard rail applications. The PVC Coating provides protection against the sunlight, while the increased Coating provides extra protection against rubbing and scrubbing, and the 7 x 7 construction provides a stiffness and low stretch that is required for guard rails.

Wire Rope Diameter Inches	Outside Diameter Inches	Weight per Foot Pounds	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds
1/8	1/4	0.04	316	W70704SP-WHITE	1,500
3/16	5/16	0.10	316	W70706SP-WHITE	3,100



Stainless Steel 1 x 19 Strand

A stiff spiral strand construction suitable for standing rigging. Applications can include yacht / sailboat rigging, architectural, guying, balustrading, cable railing and display.

1x19, Load bearing outer wires 12

Fill factor 0.76

Use of swivel is **not** permitted, not suitable for overhead lifting.

Diameter Inches	Weight per Foot Pounds	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds
1/16	0.01	316	W11902S1C-316	400
3/32	0.02	316	W11903S1C-316	1,000
1/8	0.04	316	W11904S1C-316	1,780
5/32	0.06	316	W11905S1C-316	2,800
3/16	0.08	316	W11906S1C-316	4,000
1/4	0.14	316	W11908S1C-316	6,900
5/16	0.21	316	W11910S1C-316	10,600
3/8	0.30	316	W11912S1C-316	14,800

