

PARA8K Compacted Wire Rope

8 Outer Strands, Rotation Wire Rope


PARA8K is a compacted 8 strand double parallel lay wire ropes. It offers a high strength alternative to 6 or 8 strand ropes on many crane applications including self erecting cranes erection lines, overhead cranes, pulling cables and boom pendant ropes.

8x19S (9+9+1) IWRC Load bearing outer wires 152

Fill factor 0.72

Use of swivel is **not** permitted.

Diameter	Weight per Foot Pounds	Finish	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds	Minimum Strength kN
10mm	0.32	Galvanized	2160 N/mm2	M100PROP8KB121R	22,400	100
12mm	0.50	Galvanized	2160 N/mm2	M120PROP8KB121R	32,300	144



PRO8S Rotary Swaged Wire Rope

8 Outer Strands, Rotation Wire Rope

PRO8S is an 8 strand rotary swaged construction, and offers a high strength with increased flexibility on many crane applications including self erecting cranes, ship to shore container cranes and overhead cranes.

8x19S (9+9+1) IWRC, Load bearing outer wires 152

Fill factor 0.79

Use of swivel is **not** permitted.

Diameter	Weight per Foot Pounds	Finish	Grade Tensile	Wesco Stock Code	Minimum Strength Pounds	Minimum Strength kN
9mm	0.26	Bright	2160 N/mm2	M090PRO8SA121*	16,400	80.0

* Available in Left and Right Hand Lay. Sub in 'R' for Right Hand or 'L' for Left Hand at end of code.

