

Prusik Cord

MADE IN 

Our Prusik Cord strikes the perfect balance between firm and supple. We engineered Prusik Cord so that the rope has enough grip on the climbing rope but not be so mushy that the knot locks up. This results in a smooth, controlled movement over the climbing rope and makes untying the Prusik knot easier to manage. Prusik Cord is available in 5mm to 9mm diameters, each diameter available in two reverse light and dark patterns.



Features

- ✓ Perfect balance between firm and supple
- ✓ Great grip on the climbing rope without letting the knot lock up

Specifications

Core: Nylon
Cover: Nylon

Braid: 32




Ø	Weight		Min. breaking strength		
	mm	inch	g/m	lbs/100'	daN
5	1/7	18.9	1.20	500	1,100
6	1/4	25.3	1.70	780	1,750
7	7/32	28.6	1.92	870	1,955
8	5/16	40.2	2.70	1,380	3,100
9	7/20	52.1	3.50	1,780	4,000

Premum 3-Strand Nylon



Blue
3-Strand high grade marine Nylon

Premum 3-Strand Nylon is a long-wearing, flexible and easy-to-handle rope that has greater strength and better abrasion resistance than all other 3-strand nylon lines. The highest tenacity nylon treated with our proprietary Marine Tech coating increases its wet strength and improves its fiber-to-fiber abrasion.



Ø	6mm	8mm	10mm	11mm	12mm	14mm	16mm	18mm	22mm	25mm	28mm
Diameter	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	7/8"	1"	1 1/8"
Tensile	2,100	3,000	4,250	6,000	7,500	8,800	11,650	17,150	22,300	27,700	35,800
Weight	1.60	2.40	3.50	4.60	6.30	8.00	9.60	13.70	18.70	24.30	31.10

Vintage 3-Strand



Natural
3-Strand Spun and Filament Polyester

Low stretch running rigging available in a classic shade just perfect for the traditional vessel. Excellent abrasion resistance with low stretch and high strength. Easy to splice.



Ø	4mm	6mm	8mm	10mm	11mm	12mm	16mm	18mm	24mm
Diameter	5/32"	1/4"	5/16"	3/8"	7/16"	1/2"	5/8"	3/4"	1"
Tensile	730	1,450	2,100	3,450	4,150	6,200	12,400	11,000	Call
Weight	0.67	1.67	2.60	4.40	5.10	7.30	15.00	16.50	28.75