


Galvanized 7 x 7 & 7 x 19 Class Coated Wire Rope 6 Outer Strands, Rotation Wire Rope


Galvanized PVC Coated Cables are excellent for outdoor applications with direct sunlight or wet environments. It is used for general multi purpose rigging such as safety cables, conveyor safety cables, security cables and hanger ropes.



| Wire Rope Diameter Inches | Outside Diameter Inches | Weight per Foot Pounds | Wesco Stock Code | Minimum Strength Pounds | Colours Stocked |
|---------------------------|-------------------------|------------------------|------------------|-------------------------|---|
| 1/16 (7x7) | 3/32 | 0.01 | W70702BP | 480 | Black, Clear & Yellow |
| 1/8 (7x7) | 3/16 | 0.04 | W70703BP | 1,700 | Navy Blue |
| 1/8 (7x19) | 3/16 | 0.04 | W71904BP | 2,000 | Clear, Neon Green, Red, Yellow |
| 5/32 (7x19) | 7/32 | 0.06 | W71905BP | 2,800 | Blue Screen & Neon Green |
| 3/16 (7x19) | 1/4 | 0.08 | W71906BP | 4,200 | Blue Screen, Clear, Neon Green, Red, White & Yellow |
| 1/4 (7x19) | 5/16 | 0.13 | W71908BP | 7,000 | Clear, Red & White |
| 5/16 (7x19) | 3/8 | 0.20 | W71910BP | 9,800 | Black, Clear & White |
| 3/8 (7x19) | 7/16 | 0.30 | W71912BP | 14,400 | Clear |
| 3/8 (7x19) | 1/2 | 0.31 | W71912BP | 14,400 | Orange |

Stainless Steel 316 7 x 7 & 7 x 19 Coated Wire Rope 6 Outer Strands, Rotation Wire Rope

Stainless Steel PVC Coated Cables are excellent for outdoor applications with direct sunlight or wet environments. It is used for general multi purpose rigging such as stay cables, marine ropes and architectural cables.



| Wire Rope Diameter Inches | Outside Diameter Inches | Weight per Foot Pounds | Wesco Stock Code | Minimum Strength Pounds | Colours Stocked |
|---------------------------|-------------------------|------------------------|------------------|-------------------------|-----------------|
| 1/16 (7x7) | 3/32 | 0.01 | W70702SP | 480 | Clear |
| 1/8 (7x7) | 3/16 | 0.04 | W70704SP | 1,700 | Clear |
| 1/8 (7x19) | 3/16 | 0.04 | W71904SP | 1,760 | Clear & White |
| 3/16 (7x19) | 1/4 | 0.08 | W71906SP | 3,700 | Clear |
| 1/4 (7x19) | 5/16 | 0.13 | W71908SP | 6,400 | Clear |
| 3/8 (7x19) | 7/16 | 0.30 | W71912SP | 12,000 | Clear |