


SWIVELS are used in conjunction with chain, wire or synthetic rope and slings. They are designed to be used for positioning hooks or slings onto the correct plane before lifting any product. They **SHOULD NOT** be used for rotating product while under load. They are fully forged and hot dipped galvanized product with forged markings for easy identification and traceability. Two different types are available, a Jaw End Swivel which has an eye one end and a jaw fitting for easy attachment and a Regular Swivel which has an enclosed eye at each end. They have a 5:1 factor of safety for lifting, which the Working Load Limit should **NEVER** be exceeded.

Swivels should be inspected regularly for any signs of damage, distortion or wear. Careful inspection should take place where the two sections of the swivel meet, look for any signs of fatigue, corrosion or excessive wear. A 10% reduction in material diameter is classified as excessive wear, and should be removed from service.

ProCraft Galvanized Carbon Steel Jaw End Swivel


Jaw & Eye or Jaw End Swivels can be used in conjunction with wire, chain or synthetic slings. One end has an enclosed eye while the other end has a jaw fitting for quick installation onto ropes and assemblies. They are NOT designed to rotate under load and are for load positioning only. Meets or exceeds the performance requirements of U.S. Federal Specifications RR-C-271



Stock Code	Size Inches	Working Load Limit Pounds	Dimension Inches													Weight per Piece Pounds
			A	B	C	D	E	F	G	H	I	J	K	L	M	
68JE-08	1/4	850	1.25	0.69	0.75	0.25	2.63	0.88	0.31	1.69	1.69	0.47	1.03	0.69	0.47	0.21
68JE-10	5/16	1,250	1.63	0.81	1.00	0.31	2.94	0.88	0.38	1.81	2.06	0.50	1.13	0.81	0.50	0.34
68JE-12	3/8	2,250	2.00	0.94	1.25	0.38	3.63	1.06	0.50	2.25	2.50	0.63	1.41	1.00	0.63	0.66
68JE-16	1/2	3,600	2.50	1.31	1.50	0.50	4.50	1.31	0.63	2.88	3.19	0.75	1.75	1.31	0.75	1.34
68JE-20	5/8	5,200	3.00	1.56	1.75	0.63	5.31	1.50	0.75	3.44	3.88	0.94	2.06	1.63	0.94	2.30
68JE-24	3/4	7,200	3.50	1.75	2.00	0.75	6.06	1.75	0.88	4.00	4.31	1.13	2.53	1.88	1.13	3.50
68JE-28	7/8	10,000	4.00	2.06	2.25	0.88	7.00	2.06	1.00	4.53	5.00	1.19	2.75	2.13	1.19	5.87
68JE-32	1	12,500	4.50	2.31	2.50	1.13	8.56	2.81	1.13	5.94	5.75	1.75	3.72	2.63	1.75	9.85

ProCraft Galvanized Carbon Steel Regular Swivel

Eye & Eye or Regular Swivels can be used in conjunction with wire, chain or synthetic slings. Each end has an enclosed eye for installation onto ropes and assemblies with connectors. They are NOT designed to rotate under load and are for load positioning only. Meets or exceeds the performance requirements of U.S. Federal Specifications RR-C-271



Stock Code	Size Inches	Working Load Limit Pounds	Dimension Inches								Weight per Piece Pounds
			A	B	C	D	E	F	G	H	
68REG-G08	1/4	850	1.25	0.69	0.75	1.06	2.94	1.69	0.31	0.69	0.21
68REG-G10	5/16	1,250	1.63	0.81	1.00	1.25	3.56	2.06	0.38	0.81	0.39
68REG-G12	3/8	2,250	2.00	0.94	1.25	1.50	4.31	2.50	0.50	1.00	0.71
68REG-G16	1/2	3,600	2.50	1.31	1.50	2.00	5.44	3.19	0.63	1.31	1.40
68REG-G20	5/8	5,200	3.00	1.56	1.75	2.38	6.56	3.88	0.75	1.50	2.49
68REG-G24	3/4	7,200	3.50	1.75	2.00	2.63	7.19	4.31	0.88	1.88	4.00
68REG-G28	7/8	10,000	4.00	2.06	2.25	3.06	8.38	5.00	1.00	2.13	6.25
68REG-G32	1	12,500	4.50	2.31	2.50	3.50	9.63	5.75	1.13	2.38	8.95